

HG®

tough
job

floor glue remover



far better than
any other product

can be applied to
nearly all surfaces

750 ml e

HG floor glue remover

HG "floor glue remover" is an extra strong and super-fast working glue remover, suitable for removing the most stubborn glue remains such as:

- Both solvent and water based glues
- Glues for carpets, linoleum, vinyl and PVC
- Glues for wooden or cork floors, floor tiles, and other wall and floor coverings
- Fix and mounting glue.

HG "floor glue remover" does not contain the hazardous ingredients methyl chloride and methanol, both of which are unfriendly for human health. HG "floor glue remover" can be applied without any problem to nearly all surfaces (e.g., wood, metal and concrete).

Directions for use:


- 1) First test HG "floor glue remover" on a small and inconspicuous area of the surface.
- 2) Cut carpet etc. into strips and roll up.
- 3) (Vinyl) floor covering that does not come loose should first be perforated using a pricking roller or a similar tool. The floor glue remover must be able to penetrate well into glue layer in order to remove it.
- 4) Remaining glue should be well covered with HG "floor glue remover" using a brush, for example.
- 5) After 10-15 minutes scrape off the glue using a filling knife.
- 6) Repeat the treatment, if necessary, allowing more time to work.
- 7) Finally, rinse the surface with water and allow it to dry before applying a new wall or floor covering.

Coverage: 0.5-1.0 litre per m² (depending on the glue layer and the surface)

Attention: Transport and store the jar upright. During use keep the area well ventilated. Keep in a cool and dry spot. This product is not so effective on acrylic-based glues. Do not allow the HG "floor glue remover" to dry during application or else the glue will reattach itself to the surface. 1% of the mixture consists of component(s) of unknown toxicity.

Medical personnel can request the data sheet via +31 (0)36 54 94 777

The consumer's information sheet can be obtained via www.HG.eu



HG®

tough
job

floor glue remover



far better than
any other product

can be applied to
nearly all surfaces

750 ml e

HG floor glue remover

QUESTIONS ABOUT
CLEANING AND MAINTENANCE?
www.HG.eu



DANGER H225- Highly flammable liquid and vapour.
H319- Causes serious eye irritation. **P101-** If medical advice is needed, have product container or label at hand. **P102-** Keep out of reach of children. **P210-** Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. **P233-** Keep container tightly closed. **P264-** Wash hands thoroughly after handling. **P305+P351+P338-** IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Made in The Netherlands by
HG International b.v.,
Damsluisweg 70, 1332 EJ Almere,
The Netherlands,
Tel.: +31 (0)36-5494700

relief