

HG floor tile treating matrix

Treatment	Porous tiles	Non-porous tiles	(High) gloss tiles
Removal of cement residue	HG P11 HG P12	HG P11 HG P12	HG P11
Application of basic protection (impregnation)/reducing porosity	HG P13	-	-
Protection of surface against dirt and wear	HG P14	HG P14	-
Invisible protection against dirt and staining	HG P15	HG P15	-
Regular cleaning	HG P17	HG P16 HG P17	HG P18
Intensive cleaning, remove protective layer, pre-treatment protective layer	HG P20	HG P19 HG P20	HG P19 HG P20
Removal of oil and grease stains	HG P21 HG P42	HG P21	HG P21

HG®

tiles

impregnating protector

Basic treatment for invisible protection against the penetration of dirt and grease stains, and also prevents an absorbent effect. For all types of highly to lightly porous tiles and flagstones.

product **13**

1Le

Caution: Transport and store the bottle upright. Keep in frostfree area. 2,08% of the mixture consists of component(s) of unknown toxicity **P101**- If medical advice is needed, have product container or label at hand. **P102**- Keep out of reach of children.


Medical personnel can request the data sheet via +31 (0)36 54 94 777

The consumer's information sheet can be obtained via www.HG.eu

QUESTIONS ABOUT
CLEANING AND MAINTENANCE?
www.HG.eu



contains a.o.:
preservation agents: Benzisothiazolinone,
Methylisothiazolinone



Made in The Netherlands by
HG International b.v.,
Damsluisweg 70,
1332 EJ Almere,
The Netherlands,
Tel.: +31 (0)36-5494700

0539100210006 1611

HG impregnating protector (HG product 13)

HG "tile impregnating protector" is a special, basic treatment for (new) unglazed tiles or flagstones. This unique product prevents the penetration of dirt and grease stains without affecting the original character of the tile. This product contains no silicon, dries quickly and is suitable for all types of porous and slightly porous tiles and flagstones. Can be used both indoors and out.

Directions for use:

- 1) The base must be completely clean and free of grease and dust. For the treatments that may be required: see the HG floor tile treating matrix on the side of this bottle.
- 2) The glue/cement and grouting of new floors must be completely hardened and dry. The drying time is usually 4-6 weeks.
- 3) Existing floors must be completely dry after cleaning, which will take at least 3 days. Highly porous tiles, such as terracotta, will need even more time to completely get rid of the water. For this type of tile we recommend at least 1 week. However, if the underfloor heating is switched on, a drying time of 24 hours will be sufficient. The floor heating must however be switched off for at least 12 hours prior to the treatment with this product.
- 4) The liquid should be used undiluted and preferably applied evenly in one direction with a paint roller.
- 5) If the product has not penetrated and remains on the tiles 10 minutes after application, this will need to be removed straight away with a clean, lint-free cloth.
- 6) A second treatment is recommended for very porous tiles. This second layer can be applied about 1 hour after the first treatment.
- 7) The floor can be walked on about 3 hours after the last treatment, and is completely protected 12 hours after the final treatment.

Coverage:

Highly porous tiles: ± 10-20 m² per treatment. Slightly porous tiles: ± 20-40 m² per treatment.

Maintenance:

See the HG floor tile treating matrix on the side of this bottle.

Attention:

This product may not be mixed or used in combination with HG "impregnating sealer" (HG product 4).

This product can be used for existing floors that might have previously been treated, but it is advisable to first carry out a test in an inconspicuous place. This will make it possible to establish how much product needs to be applied in order to avoid applying too much and having to remove the surplus material afterwards. It is advisable to ventilate well during the use of this product in order to speed up the drying process.

0539100310006 1611