

HG waxed parquet & wooden floors treatment matrix

| Treatment | Parquet / wooden floors (waxed) |
|---------------------------------------------------|---------------------------------|
| Protection, nourishing, waxing | HG P65 |
| Regular cleaning | - |
| Removal of wax layers | HG P67 |
| Removal of discolouration, bleach and water marks | HG P68 |



HG
P65

HG
P67

HG
P68

HG®

parquet
& wood

wax remover

Effectively removes dirty wax
from unvarnished parquet and
wooden floors.

product **67**


1Le



DANGER H226-
Liquid
and vapour. H304-
May be fatal if
swallowed and enters
airways.
H 336 -
May cause
drowsiness
or dizziness.
H372- Causes
damage to organs
through prolonged or
repeated exposure (central
nervous system). H411- Toxic
to aquatic life with long last-
ing effects. EUH066- Repeated
exposure may cause skin dryness or
cracking. EUH208- Contains Citronellal,
(R)-p-mentha-1,8-diene. May produce an
allergic reaction. P101- If medical advice
is needed, have product container or label
at hand. P102- Keep out of reach of children.
P261- Avoid breathing vapours. P264- Wash hands
thoroughly after handling. P270- Do not eat, drink
or smoke when using this product. P301+P310- IF SWALLOWED:
Immediately call a POISON CENTER or doctor/physician. P331- Do
NOT induce vomiting. P403+P233- Store in a well-ventilated place.
Keep container tightly closed. P501- Dispose of contents and container
in accordance with all local, regional, national and international regula-
tions. Contains: Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics,
aromatics (2-25%) EINECS: 919-446-0.

Made in The Netherlands by HG International b.v.,
Damsluisweg 70, 1332 EJ Almere, The Netherlands,
Tel.: +31 (0)36-5494700

| contains a.o. | |
|----------------------------|-------|
| aliphatic hydrocarbons | >30% |
| aromatic hydrocarbons | 5-15% |
| perfumes: geraniol, citral | |



0527000210006 1903

HG wax remover (HG product 67)

HG "wax remover" was developed specially for effective removal of old and dirty wax layers from unvarnished parquet and wooden flooring.

Directions:

- 1) Distribute the wax remover over a small surface area.
- 2) Rub the product well into the wax layer using a clean, lint-free (tea) towel.
- 3) Now remove the loose wax layer with a clean dry cloth.
- 4) Repeat the treatment if necessary.
- 5) Allow the floor to dry properly. After which a new wax layer can be applied if required.

Coverage:

± 15-20 m² per litre.

Caution: Transport and store the bottle upright.

Ventilate well during use and drying. Keep in frost-free area. 2,40% of the mixture consists of component(s) of unknown toxicity.

Medical personnel can request the data sheet via
+31 (0)36 54 94 777

The consumer's information sheet can be obtained via
www.HG.eu

QUESTIONS ABOUT
CLEANING AND MAINTENANCE?
www.HG.eu