

HG laminate floor treating matrix

Treatment	Laminate
Protection against wear	HG P70
Regular cleaning	HG P71 HG P72 HG P73
Intensive cleaning, remove protective layer, pre-treatment protective layer	HG P74



HG P70 **HG P71** **HG P72**



HG P73 **HG P74**

HG

laminate

laminate power cleaner

Safely and quickly removes stubborn dirt, grease and protective coatings from all laminate types.

product **74**

1Le


Attention: Transport and store the bottle upright. Keep in frostfree area. 1,8% of the mixture consists of component(s) of unknown toxicity • Medical personnel can request the data sheet via +31 (0)36 54 94 777 • The consumer's information sheet can be obtained via www.HG.eu

QUESTIONS ABOUT
CLEANING AND MAINTENANCE?
www.HG.eu



Made in The Netherlands by
HG International b.v., Damsluisweg 70, 1332 EJ Almere,
The Netherlands, Tel.: +31 (0)36-5494700

contains a.o.:	
non-ionic surfactants, phosphates	< 5%
preservation agents: Benzisothiazolinone, Methylisothiazolinone, 2-bromo-2-nitropropane- 1,3-diol	



0513400210006 1612

HG laminate power cleaner (HG product 74)

HG "laminate power cleaner" is a powerful cleaner for the safe and fast removal of stubborn dirt, grease and protective films from all types of laminate.

Directions:

For normal powerful cleaning:

Dissolve one litre in half a bucket (5L) of lukewarm water and apply it with a wrung-out mop or floor cloth, regularly rinsing it in the solution. Do not rinse or mop dry, simply leave the floor to dry on its own.

To remove HG "laminate protective coating gloss finish" (gloss coating) (HG product 70):

Pour the undiluted product into a bucket and apply it using a wrung-out mop or floor cloth. Do not make the floor too wet (See Caution). Leave to penetrate for a few minutes and if required scrub with a scrubbing brush or stiff broom. Wipe up the liquid with a clean and wrung-out mop, regularly rinsing it in clean water. Finally, mop the floor once or twice again with a wrung-out mop and clean water.

Coverage:

± 10-15 m² per litre undiluted, ± 25-50 m² per litre diluted.

Caution:

Never make laminate too wet as that could cause the seams to swell up.