

HG parquet floor treating matrix

Treatment	Parquet (varnished)
Protection of the varnish against wear	HG P51
Regular cleaning	HG P53 HG P54
Intensive cleaning, remove protective layer, pre-treatment protective layer	HG P55



HG
P51

HG
P53

HG
P54

HG
P55

HG®

parquet

p.e. polish

parquet protective coating gloss finish

For protecting with shine of the varnish layer against wear, scratching and other damage. Extremely simple to apply.

product **51**

1Le

Caution: Transport and store the bottle upright. Keep in a frost-free area. **P101-** If medical advice is needed, have product container or label at hand. **P102-** Keep out of reach of children.


Medical personnel can request the data sheet via +31 (0)36 54 94 777

The consumer's information sheet can be obtained via www.HG.eu

QUESTIONS ABOUT
CLEANING AND MAINTENANCE?
www.HG.eu

contains a.o.:

preservation agents: Benzisothiazolinone,
Methylisothiazolinone



Made in
The Netherlands by
HG International b.v.,
Damsluisweg 70,
1332 EJ Almere,
The Netherlands,
Tel.: +31 (0)36-5494700

0520000210006 1504

HG parquet gloss finish protective coating (p.e. polish) (HG product 51)

HG "parquet gloss finish protective coating" (p.e. polish) is a unique, easily applicable liquid polymer emulsion which forms a glossy, super-thin yet extremely strong protective film when dry. This protects the varnish layer of the parquet against wear, scratching and other damage. This protective film also gives an anti-slip effect.

Directions:

- 1) The surface, also for new flooring, must be completely clean and free of grease and dust. Remove any old wax, polish and polymer layers. For the treatments that may be required: see the HG parquet floor treating matrix on the side of this bottle.
- 2) Preferably apply with a wax applicator for even application (see the neck label on the front of this bottle). It is also possible to use a lint-free, clean (tea) towel wrapped around a squeegee.
- 3) Pour the liquid undiluted over the floor and then apply evenly in the direction of the wood grain without putting pressure on the wax applicator or squeegee.
- 4) Once the product has dried (after about 60 minutes), a second layer can be applied crosswise onto the first layer.
- 5) The floor can be walked on about 1 to 2 hours after the final treatment and has completely hardened after 3 days.

Coverage:

± 40 m² per litre per layer.

Maintenance:

To clean the floor treated with this protective film, use HG "parquet gloss cleaner" (wash & shine) (HG product 53), see also the HG parquet floor treating matrix on the side of this bottle.

Tip:

This product is also available in a matt version. In walkways where the protective film is more liable to wear, a new protective film can be quickly and easily applied over the existing layer, if necessary. In such cases, first clean the floor using HG "parquet cleaner" (HG product 54).

Caution:

Wait approximately 7 days before applying this product to new varnish layers. This protective film can also be used on floors not fully varnished after laying, such as laminate or veneered parquet. We do not recommend the use of this product on such floors if the top layer is made up of composite materials (such as MDF or HDF). It could then result in swelling of the composite materials in the seams. Use the HG laminate products for these floors.

0520000310006

1410